

Xerox® WorkCentre® 5030/5050

Black-and-White Multifunction System



WorkCentre 5030
shown with Duplex Automatic Document Feeder, High Capacity Feeder and Offset Catch Tray.



WorkCentre 5050
shown with Duplex Automatic Document Feeder, High Capacity Feeder and Office Finisher

	WorkCentre 5030	WorkCentre 5050
Output Speed		
Printing and Copying	Up to 30 ppm (pages per minute) 8.5 x 11 in. (A4/210 x 297 mm) LEF	Up to 50 ppm 8.5 x 11 in. (A4/210 x 297 mm) LEF
	Up to 25 ppm 8.5 x 14 in. (216 x 356 mm)	Up to 36 ppm 8.5 x 14 in. (216 x 356 mm)
	Up to 22 ppm 11 x 17 in. (A3/297 x 420 mm)	Up to 31 ppm 11 x 17 in. (A3/297 x 420 mm)
First-page-out Time (FPOT) – letter size, from platen to offset catch tray		
	As fast as 4.7 seconds	As fast as 3.4 seconds
Copy Specifications		
Copying		
Document Scanner	Duplex Automatic Document Handler (DADH) 75-sheet capacity (based on 80 gsm paper).	
Sides (input:output)	1:1, 1:2, 2:2 and 2:1	
Quantity	1 to 9,999	
Resolution	600 x 600 dpi x 8 bit	
Concurrency	Full concurrency and unlimited program ahead consistent with configuration.	

Digital Imaging	<p>AutoIQ automatic digital image quality control Auto rotation 180° or 270° when needed Image shift Edge erase Edge-to-edge copying Auto centering Original type selection (normal, text, halftone, photo) Lighter/darker Background suppression Contrast Sharpness Screening</p>
Copy Pre-Collation Memory (EPC)	128 MB (expandable to 512 MB)
Reduction/Enlargement	<p>Variable Zoom from 25 % - 400 % in 1 % increments Anamorphic Zoom Six User-Programmable percentages</p>
Special Features	<p>Auto paper select Auto reduction/enlargement to fit selected paper size Auto registration Auto tray switching Automatic job recovery Booklet creation N-up – six to one maximum for 8.5 x 11 in. / 216 x 279 mm / A4 Transparency dividers (blank or printed) Negative image Mirror image Covers insertion (front only, front and back, back only; blank or printed) Build Job Page programming of tabs or paper inserts Store and recall job programming Job interrupt Bound document copying (produce multiple sets from stored job segments) Sample set Mixed-size originals Context-sensitive help screens Stapling (single/dual) with optional finisher</p>
Foreign Device Interface (FDI) (Optional)	<p>Interface to third-party access control devices, coin machines, card readers Supports a variety of vending stations available through the Xerox Custom Application Service</p>
USB Port (Copier function only)	PC interface for upload/download of Internal Auditor data and customer device administration/software upgrade
Accessibility Option	<p>Xerox Copier Assistant™ (XCA) Software provides a PC-based alternative to the user interface touch screen. Used in conjunction with a customer-supplied PC attached via the USB port, this software provides text-to-speech, screen magnification and easy PC keyboard access to basic and advanced copy features.</p>

WorkCentre® 5030/5050

Paper Handling – Duplex Automatic Document Feeder (DADF)

Capacity ¹	75 sheets
Speed	WorkCentre 5030: Scan at rated speed (38 spm) WorkCentre 5050: Scan at rated speed (55 spm) (Letter / 8.5 x 11 in. / 216 x 279 mm / A4 long edge feed [LEF])
Paper Sizes Sensed	Statement – 5.5 x 8.5 in. (A5/148 x 210 mm long edge feed (LEF) or short edge feed (SEF)) Letter – 8.5 x 11 in. (A4/210 x 297 mm) LEF or SEF Legal – 8.5 x 14 in. (216 x 356 mm) SEF Ledger – 11 x 17 in. (A3/297 x 420 mm) SEF
Weights	13 lb to 32 lb bond (50 to 120 gsm)

Paper Handling – Two Front Loading Paper Trays

Capacity ¹	550 sheets each
Sizes	User Adjustable from 5.5 x 8.5 in. (A5/148 x 210 mm) to 11 x 17 in. (A3/297 x 420 mm)
Weights	16 lb to 110 lb index (60 to 200 gsm)
Types	Letterhead Bond Preprinted forms Plain Paper Tab Stock Envelopes (optional, Tray 2 only) Drilled/Hole-punched Heavyweight Recycled

Paper Handling – Bypass Tray

Capacity ¹	100 sheets
Sizes	User Adjustable from 4.13 x 5.83 in. (105 x 148 mm) to 11 x 17 in. (A3/297 x 420 mm)
Weights	16 lb to 80 lb cover (60 to 216 gsm)
Types	Letterhead Bond Preprinted forms Plain Paper Tab Stock Envelopes Drilled/Hole-punched Heavyweight Recycled Label Stock Transparencies

Paper Handling – High Capacity Feeder (optional on 5030; standard on 5050)

Capacity ¹	Two trays: 1,600 and 2,000 sheets
Sizes	8.5 x 11 in. (A4/210 x 297 mm) LEF
Weights	16 lb to 53 lb bond/110 lb index (60 to 200 gsm)

¹ Paper capacities are based on 20 lb/75 gsm stock; capacities will vary with different weight stocks.

WorkCentre® 5030/5050

Paper Handling – Total Capacity

Device Total Capacity ¹	4,800 sheets (with Bypass Tray, Front Loading Paper Trays and High Capacity Feeder)
------------------------------------	---

Paper Handling – Offsetting Catch Tray (Optional)

Capacity ¹	300 sheets (Letter / 8.5 x 11 in. / 216 x 279 mm / A4)
-----------------------	--

Sizes	4.25 x 5.5 in. / A6 to 11 x 17 in. / A3
-------	---

Output Option – Office Finisher Option

Capacity ¹	Top Tray – 250 sheets Stacking Tray – 2,000 sheets
-----------------------	---

Sizes	4.25 x 5.5 in. (A6/105 x 148 mm) to 11 x 17 in. (A3/297 x 420 mm)
-------	---

Weights	16 lb to 80 lb cover (60 to 216 gsm)
---------	--------------------------------------

Stapling ¹	Single (any corner) and dual Auto stapling (50 sheets maximum) Statement, letter, legal, A5, A4, A3, tabloid sizes supported
-----------------------	--

Hole Punch (Optional)	3-hole punch 2-hole Legal punch
-----------------------	------------------------------------

¹ Paper capacities are based on 20 lb/75 gsm stock; capacities will vary with different weight stocks.

Print Specifications

Network Printing – Smart Network Controller (optional)

Memory (ESS)	128 MB RAM
System Disk	Minimum 9.1 GB
Processor	Intel® Celeron® 433 MHz
Printer Languages (PDL) auto sensing/switching	<ul style="list-style-type: none"> • PCL® 6/PCL® 5e emulation • PostScript® 3™ emulation • PDF • TIFF, LCDS, SCS, XES and IPDS through third party transforms

Network Printing – Resolution (printing via CentreWare® software)

PostScript emulation: 600 x 600 dpi for 128 or 256 levels of grey:
 1,200 x 1,200 dpi and 1,800 x 1,800 dpi for 256 levels of grey via patented emulation process
 PCL emulation: 600 x 600 dpi

Network Printing – Printing Features

	Bi-directional Print Drivers Embedded web server for remote control/monitor/setup Job monitoring at the device and at desktop
	Advanced features include: Special font, Banner Sheet, Rotate Image, Offset

Network Printing – Print Driver Options

Paper Output	Job Type <ul style="list-style-type: none"> • Secure, Sample, Delay • Save and Save & Print Paper Selection by attribute (including transparency separators) Duplex (2-sided) Finishing <ul style="list-style-type: none"> • Multiple stapling positions • Hole punch (if configured) • Booklet creation • Fit to new paper size Output tray selections Store and recall driver setting
Image Options	Light/Dark Toner saver Resolution options (600 x 600 and 1200 x 1200 dpi) Reduction/Enlargement Margins (edge to edge printing) Invert Image (negative/mirror)
Layout/Watermark	N-up (16)/Multi-up Booklet Layout/Finishing Fit to new paper size Image orientation Watermark options

Printing Protocols and Networks			
Physical	Ethernet 10/100BaseT, 10BaseT, 10Base2, Token ring (IEEE802.5) – via adapter, wireless Ethernet (IEEE802.11a/b/g) – via third party adapter USB 2.0		
Operating Systems	<ul style="list-style-type: none"> • Microsoft Windows 2000, XP, Windows Server XP, Windows Server 2003, Windows Server 2008, Vista • Citrix • Novell NetWare 4.x, 5.x, 6 • Mac OS 8.x, 9.x, OS 10.3 • Solaris 2.8, 2.9, 2.10 • HPUX 11.0 • IBM AIX 4.3.3 • Linux Fedora Core 1 (Intel) • Linux Yellow Dog 3.0 		
Network Protocols Administration Protocols	<ul style="list-style-type: none"> • TCP/IPv4/IPv6, LPR/LPD, Raw IP (Port 9100), NetBIOS SMB, IPX/SPX and Net BEUI, IPP • AppleTalk/EtherTalk 		
Security Protocols	DHCP, BOOTP, SNMP, WINS, Bonjour, DDNS, SLP v2, SSDP, HTTP/S, RARP, LDAP, SMTP, POP3		
Security Protocols/Features	Protocols <ul style="list-style-type: none"> • HTTPS • SNMPv3 	Features <ul style="list-style-type: none"> • IP filtering • Unlimited Secure Print • Audit log • Image Overwrite • Data Encryption 	
Fonts	PCL: 80 scalable fonts, line printer and bitmap format line printer fonts (true type fonts) PostScript 3: 136 PostScript standard fonts (true type fonts/send fonts as/substitution table) Font Management Utility for downloading additional fonts (available for Windows and Mac)		
Print Drivers	Environment Windows 2000/XP, Windows Server 2003/2003 64 Bit, Windows Vista/Vista 64 Bit, Windows Walk-up (PS), Microsoft Certified	PCL6/5e Xerox custom graphical user interface Bi-directional features <ul style="list-style-type: none"> • Job, Paper and Toner status • Job status notification • Just in time Bi-Di • Auto population of IP address • Delete jobs 	PostScript 3 Xerox custom graphical user interface Bi-directional features <ul style="list-style-type: none"> • Job, Paper and Toner status • Job status notification • Just in time Bi-Di • Auto population of IP address • Delete jobs
	Macintosh System 8.x – 10.2	N/A	Generic PPD
	Macintosh System 10.3 and higher	N/A	Xerox custom graphical user interface Bi-directional features <ul style="list-style-type: none"> • Toner, Fuser and Xerographic module status
Xerox Mobile Express Driver (X-MED)	Makes it easy for mobile users to find, use and manage Xerox and non-Xerox devices in every new location. Plug into a new network, and X-MED automatically discovers available printers and provides status and capability information. Save a list of “favorite” printers for each location, store application print settings for use on any printer in any network, and greatly reduce mobile support calls to IT. <ul style="list-style-type: none"> • Printers are automatically discovered • Printer list can be managed based on location • Gives Bi-directional feedback device status, supplies, queue management 		

Xerox Global Print Driver (X-GPD)	<p>A truly universal print driver that lets IT administrators install, upgrade and manage Xerox and non-Xerox devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management.</p> <ul style="list-style-type: none"> • Printers are automatically discovered • Printer list can be managed based on location • Gives Bi-directional feedback device status, supplies, queue management 		
Print Submission Tools	<p>Environment Solaris 2.8, 2.9, 2.10; HPUX 11.0, IBM AIX 4.3.3; Linux Fedora Core 1 (Intel); Linux Yellow Dog 3.0</p>	<p>PCL Submission Tool only</p>	<p>PostScript 3 Submission Tool with full feature set (includes administration, GUI/TTY print driver and software installation)</p>
	<p>TIFF/PDF: Supported in Windows 98/Me/NT 4.0/2000/XP, Windows Server 2003</p>	<p>Submission Tool for any TIFF or PDF file</p>	<p>N/A</p>
Device Management			
Management Support	<p>SNMP Version 1. SNMP Version 2c and SNMP Version 3 MIB access (IETF-MIBII RFC 1213), host resources MIB RFC 2790, Printer MIB RFC v.2</p>		
Xerox CentreWare® Internet Services	<p>Allows simple remote installation setting of configuration options and management of the device</p>		
Xerox CentreWare Web	<p>A Web-based server application for network administrators that permits Web browser-based device management from any workstation, whether running Windows, UNIX or any other operating system. Works with any SNMP-managed printer from any manufacturer. Provides help with device discovery and installation, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management. Requires Windows XP or 2000 (Professional or Advanced Server) Windows 2003 and Internet Explorer 6.0 and higher</p>		
Novell NDPS/NEPS (gateway for WorkCentre)	<p>Server gateway application: centralized management tool</p>		
Xerox CentreWare for Unicenter TNG	<p>Provides added identification to the general discovery performed by Unicenter TNG and the ability to see the WorkCentre under a Unicenter TNG Business Process View</p>		
Xerox CentreWare for Tivoli NetView	<p>Provides for the identification of Xerox WorkCentre multifunction systems in the general discovery performed by Tivoli NetView</p>		
Xerox CentreWare for HP OpenView	<p>Provides for the identification of Xerox WorkCentre multifunction systems in the general discovery performed by HP Openview Provides traps and message updates to the Open View alarm browser and the ability to launch CentreWare Internet Services for device management directly from OpenView</p>		
Xerox Barcode Pro PS <i>Information available at www.xeroxofficesap.solutions.com</i>	<p>Enables intelligent PostScript printing on Xerox multifunction systems by storing Xerox software, as well as, the barcode fonts on the printer hard disk. Enables the printing of barcodes from any application (SAP R/3 client or mainframe) that supports PostScript printing. Automatically calculates the check digit, places start/stop and middle bar characters in the data string, compresses and encodes the data string, and rotates the barcode through 90 or 270 degrees.</p>		

<p>Xerox Device Types for SAP R/3 Environment are available at www.xeroxofficesapsolutions.com</p>	<p>Simplifies printing in SAP R/3 environments by providing users of SAP R/3 3.x, 4.x, 4.5x, 4.6x, SAP Enterprise 4.7x, ERP applications with enhanced WorkCentre printing functionality (PostScript and PCL):</p> <ul style="list-style-type: none"> • One- to Two-sided printing • Finishing provides single or dual stapling • Tray pull location from any tray • # of copies – provide the ability to print multiple copies • Paper Type and color – provide ability to select different paper types and paper colors, such as transparency, red, etc. • Print security via PIN ID capability at the WorkCentre • Network Accounting (JBA) – Provides capability to add Job Based Accounting User IDs to SAP print jobs • Printer banner sheet – Provide the ability to enable/disable printer banner sheets • Barcode printing – Xerox standard PostScript device types available at www.xeroxofficesapsolutions.com supports Intelligent Barcode Printing with Xerox Barcode Pro PS. This Barcode Pro PS can be purchased at www.font.net
<p>Xerox SAP R/3 Intelligent Barcode Utility (optional) Purchase via www.font.net</p>	<p>Provides built-in process intelligence that allows the printing of barcodes on any appropriately configured PostScript printer on the SAP R/3 4.1x, 4.5x, 4.6x and within Latin-1 (ISO8859-1) SAP system code pages only. Used in conjunction with Xerox PostScript Device Types for SAP R/3 environment and Xerox Font Center Barcode Fonts. Utility enables automated checksum calculation, placement of start/stop characters, encoding of data string and data compression.</p>

CentreWare Internet Services – Integrated device Web page

<p>Device Status</p>	<p>Web server embedded on Controller</p> <ul style="list-style-type: none"> • Tray status/contents • Consumables status • Alerts
<p>Job-Print Queue Viewing</p>	<p>Complete job print queue management</p>
<p>Job Submission</p>	<p>Print ready files PS, PCL (TIFF, PDF with Copier/Printer only) Output feature selection (2-sided, staple, fold, hole punch, paper select) Delivery options (Immediate, proof, delay and secure)</p>
<p>Device Administration</p>	<p>Allows simple, remote installation setting of configuration options and management of the device</p>
<p>Scan Template Management</p>	<p>250 templates can be created Create device specific CentreWare scan templates Select confirmation sheet options Share scan templates via device cloning</p>
<p>Browsers</p>	<p>Netscape 6.2, 7.x (Mozilla 1.x) Internet Explorer 5.5.x, 6.x, 7.x Safari 1.x Mozilla Firefox 1.x</p>
<p>Support</p>	<p>Online support available via web page</p>

Scan Specifications	
Scanning	
Concurrency	Scan while the system is printing, copying, or while it is transferring scan to network or fax jobs
Input Speed	Scan at up to 85 ipm (Black and White) – 8.5 x 11 in. (A4/210 x 297 mm) LEF at all resolutions
Resolutions	<p>DPI Options</p> <ul style="list-style-type: none"> 600 x 600 dpi 400 x 400 dpi 300 x 300 dpi 200 x 200 dpi 100 x 100 dpi 72 x 72 dpi <hr/> <p>Scan Presets</p> <ul style="list-style-type: none"> • Archival Record (Normal Quality - Smallest file size) – 100 x 100 • For Sharing and Printing (Normal Quality - Small file size) – 200 x 200 • For High Quality Printing (High Quality - Large file size) – 300 x 300 • For OCR (High Quality - Large file size) – 300 x 300 • Simple Scan (Normal Quality - Small file size) – 200 x 200 <hr/> <p>Quality/File Size</p> <ul style="list-style-type: none"> • Normal Quality (Small file size) • Higher Quality (Large file size) • Maximum Quality (Largest file size)
Maximum Scan Area	11 x 17 in. (A3/297 x 420 mm)
File Formats	TIFF 6.0 with G3 MH, G4 MMR, MRC or JPEG compression (single page or multiple pages) PDF (image only with G3 MH, G4 MMR, JPEG or JBIG2 compression), PDF/A and XPS
Network Scanning (optional)	
Capability	<ul style="list-style-type: none"> • Enables device-specific network scan workflows (destination templates) to be easily created and edited via CentreWare® Internet Services • Scan to Home displays one template and populates with the user's directory path after authentication • Scan to file • Scan to network server / directory • Scan to Windows XP client via Windows Image Acquisition (WIA) or TWAIN driver downloadable from www.xerox.com
Network Protocol	Novell (NCP via IPX/SPX) FTP Microsoft SMB via TCP/IP HTTP/HTTPS
Document Management Fields (Metadata)	<p>Features only available in Network Scan to File Templates:</p> <ul style="list-style-type: none"> • 1-6 user programmable metadata fields per network scan to file templates and unlimited fields within the template • Metadata Fields consists of field name, display at the LUI or not, default value and other configurations <p>Customized fields viewed on user interface Variable data entered using virtual keyboard at device</p>
Scan Template Management	Share scan templates among WorkCentre via device cloning Scan template management (250 templates) with CentreWare Internet Services Select confirmation sheet option
Scan Features	Build job for Scan to file and Scan to Email (enables special programming for different pages in one document – can be used for inserts, mixing input from the document glass and document feeder), Duplex scanning, Auto detect document size, Scan mixed size originals, scan to edge.

Scan to Email (optional)

Capability	Scan to email (manual address entry or directory (Exchange/Notes/LDAP) address searching (internal address book or Public address book – up to 128 recipients)
Network Protocol	SMTP MIME encoded
Scan Features	Email signatures (6 lines each of 128 character max), email message body (user configurable), email CWIS confirmation sheet options

Network Scanning Software Solutions

Scan to PC Desktop Workgroup Edition SE (optional)	A desktop offering that provides document imaging, archiving, editing and organization tools ScanSoft PaperPort SE – image viewing and file management software ScanSoft OmniPage SE – offer desktop/client installation – OCR and file format conversion software Image Retriever – provides fully automated retrieval of scanned images direct from WorkCentre to individual desktops
Scan to PC Desktop Workgroup Edition Professional (optional)	A desktop offering that provides advanced document imaging, archiving, editing and organization tools. ScanSoft PaperPort Professional image viewing and file management software <ul style="list-style-type: none"> • Complete PDF functionality • Secure PDF workflow of all scanning applications ScanSoft OmniPage Pro Office (for desktop/client installation) Professional OCR software for digital archiving and document conversion Image Retriever – provides fully automated retrieval of scanned images direct from a scan enabled Xerox WorkCentre to individual desktops. Also includes an email inbox polling capability.
SMARTsend ² (optional)	Server base document routing software that supports multiple scan-enabled multifunctional systems Enables transformation, distribution and routing of scanned documents Workflow creation via Web browser-based task creation (destinations, devices, document attributes – 20 file types including PDF, workflow settings, workflow summary) <ul style="list-style-type: none"> • Scan to File Destinations: email, Microsoft NetWare folder, network folder, FTP, Microsoft Exchange 2000 web folders, web URL, remote printers • Scan to Document Repository Destinations: DocuShare, Domino, Domino.doc, Microsoft SharePoint, Hummingbird DNS, Open Text Livelink, Documentum, Interwoven Work Site Workflow initiation via device scanning user interface (template selection at device UI) Adding of Metadata information
SMARTsend ² Professional (optional)	Everything in SMARTsend, plus: <ul style="list-style-type: none"> • Workflow initiation via Paperware (Scan coversheets) • Server-based Optical Character Recognition (OCR) • Searchable PDF • Scan to Internet fax file destination • TrueMatch patented search technology

² Features, configurations and options vary by location.

Fax Specifications

Fax Options – Walkup Option (One Line)

Compatibility	ITU (CCITT) Group 3
Memory	256 MB
Speed/Modem(s)	1 or 2 V.34 modems: 33,600bps. Less than 4 seconds per page transmission time, ISDN via third party adapter
Compression/Speed	MH/MR/MMR/JBIG/G3/Super G3
Fax Send Features	<p>Quality/Resolution</p> <ul style="list-style-type: none"> • Original type: Normal, text, half tone, photo, lighter/darker, background suppression • Fax – off Platen, mixed sizes or Bound/Book <p>Auto Send (Up to 5)</p> <p>Audio line monitor</p> <p>Transmission options (Report/Header)</p> <p>Reduce/Split large documents</p> <p>Cover letter</p> <p>Delayed send</p> <p>Build Job (up to 1000 images)</p> <p>Polling</p>
Fax Receive Features	<p>One- or two-sided printing</p> <p>Stapled or unstapled, hole punch</p> <p>Receive print mode – Manual (size, margin, stock, header)/Auto</p> <p>Auto answer delay</p> <p>Secure receive</p> <p>Junk fax prevention</p>
Fax Reports	<p>Activity</p> <p>Dial directory</p> <p>Group directory</p> <p>Options</p> <p>Pending Jobs</p>
Fax Mailboxes	<p>Up to 100 password-protected</p> <p>Poll Remote mailboxes (up to 255) password-protected</p>
Auto Dialing Features	<p>Speed Dials</p> <ul style="list-style-type: none"> • 200 <p>Group Dials</p> <ul style="list-style-type: none"> • Up to 100 groups with up to 200 recipients per group <p>Auto redial</p> <ul style="list-style-type: none"> • Up to 14 attempts • Up to 25 min intervals • Batch Send (up to memory capacity)
Resolutions	<p>200 x 100 dpi (Standard)</p> <p>200 x 200 dpi (Fine)</p> <p>300 x 300 dpi</p> <p>200 x 400 dpi</p> <p>400 x 400 dpi</p> <p>400 x 600 dpi</p> <p>600 x 600 dpi (Super Fine)</p>

Fax Options – Internet Fax Enablement (optional)

Capability	Direct document transmission to remote Internet Fax machines or e-mail clients (SMTP) Reception and automatic printout of documents sent via e-mail from remote Internet Fax machines or e-mail clients
Maximum Scan Area	11 x 17 in. (A3/297 x 420 mm)
Address Directory Access	Corporate address list via LDAPv3 Downloaded address list (comma-separated file format) Internal LDAP or Public address book
File Formats	TIFF-FX profiles S, F with G3 MH or JPEG compression PDF (image only) with G3 MH, G4 MMR or JPEG compression PDF and Multi TIFF
Resolutions	600 x 600 dpi 400 x 400 dpi 300 x 300 dpi 200 x 200 dpi 200 x 100 dpi 100 x 100 dpi 72 x 72 dpi
Network Protocols	SMTP POP3 (RFC 1939)
Compliance	ITU-T T.37 compliant
Features	Signature (SA configurable –16 lines each of 128 character max) Delivery Confirmation <ul style="list-style-type: none"> • Email receipt option • Confirmation reply option • Cover sheet option • Subject (248 characters) • User configurable message body

Fax Options – Network Fax Server Enablement (optional)

Capability	Provides walk-up faxing and hard copy output of received faxes when integrated with fax server applications (fax server and software must be purchased separately from supplier). Transmission speeds, number of lines, compatibility and compression are dependent on fax server configuration (via SMTP).
Maximum Scan Size	11 x 17 in. (A3/297 x 420mm)
Network Protocols	Novell (NCP via IPX/SPX) FTP Microsoft SMB via TCP/IP HTTP/HTTPS SMTP
Fax Send Features	One- or two-sided scanning (up to 11 x 17 in. (A3/297 x 420 mm)) Phone number entry Add to send list (50 numbers maximum) Delay send (specific time) Resolution selection (fine, standard) Image quality selection (normal, text, lighten/darken, photo, background suppression, seven levels of contrast, seven levels of sharpness)

WorkCentre® 5030/5050

Fax Print Features	One- or two-sided printing Quantity Staple on/off Collate on/off Secure print on/off Finisher output tray selection (top tray or main tray)
Supported Network Fax Vendors	Multiple vendors, certified by the Xerox Alliance Partner Program. For details visit www.xerox.com

Device Management Specifications

Accounting Features – Internal Auditor

Tracking	Copy usage
Accounting	Up to 2,150 User accounts Up to 5,925 General accounts Up to 256 Group accounts
Features	Audiron report printout, ability to upload/download account and usage data via direct connection using Microsoft Windows based software

Accounting Features – Network Accounting Enablement Kit (optional)

Enhanced network accounting with up to the minute data on how the WorkCentre system is being used; comprehensive management and enterprise scale tracking and reporting of device usage of copy, print, scan and server fax. Various options available through Xerox Business Alliance Partner solutions. For details visit www.xerox.com
Security enhancements with the addition of HTTPS protocol support
WorkCentre requests account authentication from 3rd party server enabling larger databases of users and accounts

Security – Review the Supplemental Security Brochure for Details

Authentication	Secure device login with network user name and password Supports Kerberos (Windows 2000/UNIX/Windows Server 2003) SMB (Windows NT 4.0/Windows 2000/Windows Server 2003) Novell over IP/IPX (Novell NetWare 4.x/5.x/6.x) LDAP Secure Access Common Access Card enablement (CAC)
Features	IPv6 Ready (Phase 2) Disk Image Overwrite – Immediate, On Demand, Scheduled HTTPS (SSL) SNMP V3 Network Authentication Device Access Password Protection IP Filtering Audit Log Full Disk Encryption Secure Print Fax Security Image Overwrite (Immediate, On Demand and Scheduling)
Common Criteria Certification	Common Criteria Certification provides independent, objective validation of the reliability, quality, and trustworthiness of IT products. It is a standard that customers can rely on to help them make informed decisions about their IT purchases. Common Criteria Certified version available.

Secure Access Unified ID System (optional)

Secure Access Unified ID System adds an advanced layer of security at the device by enabling users to log-in to a Xerox MFP system with a swipe of their magnetic or proximity ID card. When combined with Follow You Print functionality, Secure Access allows private print jobs to be accessed from any Xerox printer or MFP on your network.

Common Access Card Enablement

Common Access Card Enablement is a solution that increases security of government facilities and critical information through the use of smart identification cards. (Available only in U.S. and certain configurations.)

Machine Specifications

Monthly Duty Cycle

5030 – up to 125,000 pages
5050 – up to 200,000 pages

Basic Configurations†

WorkCentre 5030:
Digital Copier with Duplex Automatic Document Feeder, 2 trays, stand and 128 MB EPC memory
WorkCentre 5050:
Digital Copier with Duplex Automatic Document Feeder, 2 trays, High Capacity Feeder and 128 MB EPC memory

Accessory Options

One-line fax option
Xerox Copy Assistant
Office Finisher
Two-hole legal punch option
Three-hole punch option
Foreign Device Interface
Offsetting Catch Tray
Network Accounting Enablement
Network Scanning With E-Mail
Network Fax Server Integration
Internet Fax
Scan to PC Desktop Client Software
Copy Pre Collation RAM Upgrade (256 MB)
Envelope Insert Kit (Tray 2)
Convenience Stapler (50 sheets)
SMARTsend
SMARTsend Professional
Smart Print Controller (Optional)
High Capacity Feeder (Optional on WorkCentre 5030)

Electrical Requirements

110-127 Volt Nominal, 60 Hz, 12A

Power Consumption

WorkCentre 5030**

WorkCentre 5050**

Running

< 1151 watts

< 1247 watts

Standby

< 255 watts

< 284 watts

Low Power Mode

< 160 watts

< 180 watts

Sleep Mode

< 80 watts

< 95 watts

Warm Up

99 seconds (maximum)

99 seconds (maximum)

Low Power Recovery

20 seconds (maximum to Ready to Scan)

20 seconds (maximum to Ready to Scan)

* Features, configurations and options may vary by location

** Digital Copier with SMART Print Controller, Office Finisher and fax options fitted.

Dimensions and Weights

	Width	Depth	Height	Weight
Fully Configured with Office Finisher	58.7 in. / 1,490 mm	28.3 in. / 720 mm	43.9 in. / 1,115 mm	399 lbs / 181 kg

Space Requirements

	Width	Depth	Height
Fully Configured with Office Finisher– Moveable Surface	88.3 in. / 2,245 mm	67 in. / 1,700 mm	78 in. / 1,981 mm

Certifications

FCC Class A Compliant (U.S.), DOC Class A Compliant (Canada)
 UL Listed (UL 1950–1:2000)
 CB Certified (IEC 60950 / EN 60950)
 Novell Tested and Approved
 Windows Hardware Quality Labs

Supplies

Description	Order Number	No. per Box	Expected Yield
Toner Cartridge	006010146	2	> 30,000 at 6 % area coverage per bottle
Staple Cartridge	108R00493	3	5,000 per cartridge (15,000 staples)
Staple Cartridge (for Convenience Stapler) <ul style="list-style-type: none"> • Complete Cartridge • Refill Cartridge 	008R12964 008R12941	1 3	5,000 per cartridge 5,000 per cartridge (15,000 staples)

SMart Kits

Description	Order Number	No. per Box	Expected Yield
Fuser Module (includes ozone filter) North America	109R00636	1	350,000
Xerographic Module – Metered	113R00608	1	200,000
Xerographic Module – Sold	113R00610	1	200,000
Document Handler Feeder Rolls	113R00651	1	150,000 feeds

WorkCentre® 5030/5050



©2009 Xerox Corporation. All rights reserved. Xerox® and the sphere of connectivity design, CentreWare®, WorkCentre® and Copier Assistant are trademarks of Xerox Corporation in the United States and/or other countries. PostScript is a registered trademark of Adobe Systems Incorporated in the United States and/or other countries. Other marks are trademarks or registered trademarks of the companies with which they are associated. In support of Xerox's environmental leadership goals, these models may contain some recycled components that are reconditioned. Product information and/or specifications are subject to change without notice. 6/09 610P727770C WS355-01UE

