

LEXMARKTM

C750



The Lexmark C750 offers businesses the impact of color with the speed and reliability of a monochrome workgroup printer at an affordable price.

- Fast, 20 ppm color output for high-volume printing needs
- True 1200 x 1200 dpi for nearly flawless results
- Laser technology with a 350 MHz processor to process large jobs quickly
- Accurate and consistent color quality



Breaking the rules of color printing.

Lexmark C750 Color Laser Printer



Part Numbers

- C750: 13P0001
- C750n: 13P0051
- C750dn: 13P0251
- C750dtn: 13P0151
- C750nTR: 53A0358
- C750dtnTR: 53A0359

Technology

- Color Laser

Speed

- Up to 20 pages per minute (letter and A4)
- Less than 20 seconds time to first page

Print Quality

- 2400 Image Quality
- 1200 x 1200 dpi

Processor

- 350 MHz RISC

Memory

- 64MB/512MB (C750, C750n, C750dn, C750nTR)
- 128MB/512MB (C750dtn, C750dtnTR)

Connectivity

- USB port standard (all models)
- Bidirectional parallel port (C750)
- 10/100BaseTX Ethernet standard (C750n, C750dn, C750dtn)
- Token Ring standard (C750nTR, C750dtnTR)
- One internal solutions port
- C750 supports the MarkNet™ X2000 series of external printer servers
- C750 supports the MarkNet N2000 series of internal print servers
- C750 supports the MarkNet N2003 and N2004 series of internal fiber print servers
- Optional Tri-Port Adapter with RS-232/422 Serial, LocalTalk and IR Adapter ports
- Optional USB/Parallel 1284-C

Interface Card

- Optional RS-232-C Serial/Parallel 1284-C Adapter
- Optional Coax/Twinax Adapter for SCS

Compatibility

- PostScript 3 emulation standard
- PCL 5c emulation standard
- PCL 6 emulation standard

Font Selection

- PostScript 3 emulation
 - 156 scalable fonts
- PCL 6 emulation
 - 84 scalable fonts
 - 2 bitmapped fonts

Paper Handling

- Media sizes:
 - Standard support including letter, legal, A4, A5, JIS B5, executive, folio, statement, and custom sizes 5.5" x 8.27" to 8.5" x 14" (139.7 mm x 210 mm to 216 mm x 355.6 mm)
 - Expanded custom sizes 2.75" x 5" to 9.01" x 14" (69.85 mm x 127 mm to 229 mm x 355.6 mm) and 5.83" x 7.17" to 8.5" x 14" (148 mm x 182 mm to 215.9 mm x 355.6 mm) with the Universally Adjustable Tray
- Media types:
 - Plain paper, bond, envelopes, card stock, transparencies, and paper labels
- Media weights:
 - 16 lb. to 47 lb. bond (60 g/m² to 176 g/m² bond)
 - Up to 90 lb. card stock (Up to 337 g/m² card stock)
- Input (std/max): 600/3,100 sheets
- Standard input sources:
 - One 500-sheet tray (C750, C750n, C750dn, C750nTR)
 - Two 500-sheet trays (C750dtn, C750dtnTR)
 - One 100-sheet multipurpose tray on all
- Maximum input sources: 5
 - The 2 standard inputs plus 3 additional drawers (500-sheet) (C750, C750n, C750nTR)
 - The 3 standard inputs plus 2 additional drawers (500-sheet) (C750dtn, C750dtnTR)

- One high-capacity feeder (2,000-sheet)*

- Output (std/max): 250/3,900 sheets
- Optional 5 bin mailbox
- Optional 650-sheet stacker
- Optional 3,000-sheet finisher**
- Optional duplex unit for two-sided printing

Supplies

- The Lexmark C750 ships with 6,000-page*** print cartridges and Prebate™ cartridges

- Waste toner bottle 180,000 black/50,000 color

Other Supplies

- 15,000-page*** high yield print cartridges and high yield Prebate print cartridges
- Staple cartridge

Operating Systems

- Microsoft Windows 95, 98, Me, 2000, NT, UNIX, Macintosh OS, Linux and others
- See www.lexmark.com for complete list

Size/Weight

- 23.8" x 18.5" x 20.8" (W x D x H)
- (604 mm x 471 mm x 528 mm)
- 105 lb. (47.7 kg)

Acoustics

- 51 dBA printing (C750, C750n, C750nTR)
- 53 dBA printing (C750dn, C750dtn, C750dtnTR)
- 42 dBA idle

Duty Cycle

- Up to 60,000 pages per month maximum one time usage
- 10,000 pages per month maximum continuous usage

Warranty

- 1-year LexOnSiteSM

**An optional 500-sheet drawer is required when utilizing the 2,000-sheet high-capacity feeder and a duplex unit. The first option under the duplex unit must be a 500-sheet drawer*

***This device has not been authorized as required by the rules of the Federal Communications Commission. This device is not, and may not be, offered for sale or lease, or sold or leased, until authorization is obtained. Receipt of authorization is expected in March 2002.*

****Yield is based on approximately 5% print coverage*



Lexmark International, Inc. is a global developer, manufacturer and supplier of printing solutions and products, including laser, inkjet and dot matrix printers and associated consumable supplies for the office and home markets. The company is a wholly owned subsidiary of Lexmark International Group, Inc. (NYSE: LXX). Lexmark is on the Internet at www.lexmark.com. Specifications subject to change without notice. Lexmark, Lexmark with diamond design, Prebate and MarkNet are trademarks of Lexmark International Inc., registered in the United States and/or other countries. LexOnSite is a service mark of Lexmark International, Inc. Apple, Macintosh and LocalTalk are trademarks of Apple Computer, Inc., registered in the U.S. and other countries. PCL is a trademark of Hewlett-Packard Company. Microsoft and Windows are registered trademarks of the Microsoft Corporation. Windows NT is a trademark of the Microsoft Corporation. PostScript is a registered trademark of Adobe Systems Incorporated. PS/2, Operating System/2, AIX, Application System/400, OS/400, Operating System/400, and RISC System/6000 are registered trademarks of the International Business Machines Corporation. All other trademarks are the properties of their respective owners. As an ENERGY STAR Partner, Lexmark International, Inc. has determined that this product meets the ENERGY STAR guidelines for energy efficiency. ENERGY STAR is a U.S. registered trademark.

LEXMARK
Passion for printing ideas.™

©2001 Lexmark International, Inc.
All Rights Reserved
71C-6308
PC31424