



Sometimes you want
a challenge.

Sometimes you don't.

Lexmark C920

Outstanding A3 colour made easy

Performance and quality

Benefit from high-volume colour printing, pairing tireless performance with superior image quality.

Total flexibility

Handle an array of media formats and sizes with ease, plus benefit from quality-control features and a wide range of finishing options.

True peace of mind

Ensure your sensitive documents always stay in the right hands, with state-of-the-art data security features.

Up to 36 ppm in mono
Up to 32 ppm in colour

2400 IQ

USB direct interface

We make printing easy

LEXMARKTM

Lexmark C920/C920n/dn/dtn

Enhanced productivity to empower your workgroup

Achieve outstanding colour printing without compromising performance – even on wide formats! In addition to crisp, clear results, the Lexmark C920 delivers A4 colour output in as fast as 36ppm, and advanced colour management tools to help you control costs. Plus, a powerful 1GHz processor delivers enough punch to print your first page in as little as 9.5 seconds flat.

The sky's the limit

Produce eye-catching documents in just about any format you need, including transparencies and 1.2m banners! Automatic colour correction and precision-printing modes give you full control over image quality.

Top-notch security

Solid transmission security ensures total peace of mind for your most sensitive documents. For even more reassurance, you can count on a range of features, like advanced printing lockout and 'expiration time' programming.

The operating panel is 'key'

More than just attractive, the new operating panel is easy for everyone. And it even includes a USB port for simple PC-free printing. Users just slide in their USB memory device key, locate their document on the large LCD screen and start printing. It's that simple!

Easy on you and your budget

Keep everything running smoothly. Maintenance is minimal with the increased page yield and reliability of long-life cartridges, while colour permission settings can significantly optimise toner consumption.



*With special configuration

Models available

C920 – Standalone
C920n – Network
C920dn – Duplex, network
C920dtn – Duplex, network, extra 550-sheet tray

With our innovative solutions and services, we help you **PRINT smarter, MOVE information faster and MANAGE output more efficiently** across your enterprise. Ask your local Lexmark representative for more information.



Technology	LED
Speed	Mono: 36 ppm Colour: 32 ppm
Time to first page	Mono: 9.5 seconds Colour: 13.5 seconds
Processor	1GHz
Memory	Standard: 256 MB for std model; 512 MB+ for n, dn, and dtn models Optional: 256 MB / 512 MB
Resolution	2400 Image Quality
Duty cycle	200K pages per month maximum 1.5 million pages life

Standard input	C920: 550 sheets + 100 sheets MPF C920n: 550 sheets + 100 sheets MPF C920dn: 550 sheets + 100 sheets MPF + duplex C920dtn: 2 x 550 sheets + 100 sheets MPF + duplex
Maximum input	5,300 sheets
Standard output	650 sheets
Finishing (all optional)	Duplex Printer cabinet 1,100-sheet staple & punch finisher 3,000-page high-capacity feeder
Media supported	Standard: paper, cardstock, labels and glossy transparencies: 60 to 216 g/m ²
Paper size	A4, Letter, Legal, A3+, A5, Banner

Connectivity standard	All models: USB port, high-speed bi-directional parallel port, 1 internal solution port Network models: Integrated Ethernet, USB & Parallel, 1 ISP port
Network management software	MarkVision Professional
Compatibility	PostScript Level 3 Emulation PCL 6 Emulation with colour extension PPDS Migration Tool PDF 1.5 ImageQuick (PDF, TIFF, JPEG)
Operating systems supported	Microsoft Windows 9x, ME, NT, 2000N XP, Server 2003 Novell NetWare 3.2, 4.2, 5.x, and 6.x UNIX: HP-UX 11.0, IBM AIX 4.33, 5.1, Sun Solaris 2.6, 7, 8, 9, other systems LINUX: Red Hat 7.2, 7.3, 8.0, SuSE 7.2, 7.3, 8.0, other systems Mac OS 8.6, 9.x, X IBM AS/400 version 4 release@ or later
Font selection	158 PostScript Scalable Fonts 89 PCL 6 Emulation Scalable Fonts 2 PCL 6 Bitmapped Fonts PPDS - 39 Scalable Fonts, 5 Bitmapped Fonts
Electronic forms support	Forms Card DLE + additional flash memory or hard disk
Optional cards	Bar Code Card, IPDS
Optional adapter	External print servers: Wireless, Ethernet 10/100 base Tx, Ethernet 10 base 2, Token Ring Internal print servers: Token Ring, Fast Ethernet, Gigabit Ethernet, Fibre Ethernet, Wireless, Coax/Twinax Adapter for SCS
Local ports	1284C Parallel/USB adapter, 1284C Parallel/ RS - 232C serial adapter storage, hard disk adapter
Special features	Security features: Secure management with Markvision Professional, secure network communications, confidential print, print encryption, digital-signed firmware update files, encryption for optional internal hard disk drives, operator panel menu lockout, printing lockout Total control of colour: Colour print permission, coverage estimator, colour saver, toner saver, proof then print, customer mono-only driver, black & white lock mode

Guarantee	Base guarantee: One year, LexRepair, response time next business day Extended guarantee: 1, 2 or 3 years, LexRepair, response time next business day
Optional services	Installation service, de-installation service, hardware and software training
Supplies	Ships with 8K-pages CMYK toner cartridges* 15K pages Black toner cartridge (aftermarket)* 14K pages CMY toner cartridges (aftermarket)* 28K colour photo developer kit* 28K black photo developer* 15K oil coating roller (ships with black cartridge)* Transparencies, Banner Paper, Outdoor Media and Glossy Paper

Size (H x W x D)	512 mm x 695 mm x 711 mm	Cost saving & environmental features	Energy Star compliant Blue Angel Taiwan Green Mark Canadian Environmental Choice Packaging Green Dot WEEE RoHs, from November 2005
Weight	80.5 Kg		
Acoustics	45 dB(A) ready 55 dB(A) duplex printing		
Power & electric specifications	290 watts printing 125 watts standby		

*Yield at approximately 5% coverage

Specifications are subject to change without notice. Lexmark, Lexmark with diamond design is trademark of Lexmark International, Inc. registered in the United States and or other countries. All other trademarks are the properties of their respective owners.

www.lexmark.com

LEXMARK
TM

INFOLASH • www.infolash.fr

PN 8047522