

HL-5050

- High speed, feature rich Windows®/MAC™ Laser Printer
- 16ppm Print Speed
- Optional Lower Tray
- 16MB Standard Memory
- PostScript Level 3 Language Emulation
- PCL 6

Versatility

The printer that can take on any task



••••• We're always at your side

The hard-working printer for hard-working people.

In today's busy office the humble printer can be expected to tackle any number of different tasks, from simple letters and memos to complicated, memory hungry documents, with the same speed and efficiency. And that's exactly where some printers simply can't take the pace.

If you need a printer every bit as sophisticated as the material you want it to print, then you need the Brother HL-5050. Equally at home in either PC or MAC environments, the HL-5050's generous 16MB memory and handy PostScript Level 3 Language Emulation feature, enables it to handle large spreadsheets and graphic heavy documents with considerable ease. It also offers professional quality (2400x600dpi), rapid turn-around (up to 16 pages a minute), and generous output (as many as 20,000 pages per month). Features guaranteed to ensure that the HL-5050 will work just as hard as you do.

Technical Specifications



GENERAL

Print Speed	Up to 16ppm (A4)
First Print Time	Less than 12 seconds
Resolution	2,400 x 600dpi (HQ1200) 600 x 600dpi 300 x 300dpi

CONTROLLER

Processor	133MHz
Memory	16MB, expandable up to 144MB
Interface	"Hi-speed USB 2.0", IEEE 1284 Parallel
Optional Interface	10/100BaseTX Ethernet (to order quote: NC-2100p)
Network Protocols	TCP/IP, NetBEUI, AppleTalk
Emulation	PCL [®] 6, BR-Script3 (PostScript [®] 3 Language Emulation), IBM Proprinter XL, Epson FX-850
Resident Fonts	PCL [®] : 66 Scalable Fonts, 12 Bitmap Fonts
Barcodes	11 Barcodes

SOFTWARE

Windows [®]	PCL [®] / BR-Script 3 Driver for Windows [®] 95/98/Me/NT [®] 4.0/2000/XP
Macintosh [®]	Mac [®] OS 8.6-9.2, OS X 10.1/10.2
Linux	GDI Driver and BR-Script 3 Driver
Utilities	Interactive Help

CONTROL PANEL

3 Colour Status LED
Go and Job Cancel button
Toner, Drum, Paper, LED

PAPER HANDLING

Input Paper Capacity	250 Sheets 50 Sheet Multi-purpose Tray
Optional Input Paper Capacity	250 Sheets (to order quote: LT-5000)
Output Paper Capacity	150 Sheets Face Down 25 Sheets Face Up
Duplex	Manual Duplex

MEDIA SPECIFICATIONS

Media Types (Paper Tray) (Manual Feed Slot)	Plain, Bond, Recycled Paper and Transparencies Plain, Bond Recycled Paper, Transparencies, Labels and Envelopes
Media Weights (Paper Tray) (Manual Feed Slot)	60 – 105g/m ² 60 – 161g/m ²
Media Sizes (Paper Tray) (Manual Feed Slot)	A4, Letter, B5 (ISO), A5, B6 (ISO), A6, Executive and Legal Custom: 69.8mm to 220mm x 116mm to 406.4mm

SUPPLIES

Toner (Standard Yield) (High Yield)	3,300 A4/Letter Pages @ 5% coverage (TN-7300) 6,500 A4/Letter Pages @ 5% coverage (TN-7600)
Drum	20,000 A4/Letter Pages (DR-7000)

DIMENSION / WEIGHT

Dimension	(382mm width) x (401mm depth) x (252mm height)
Weight	11.5kg

OTHERS

Power Consumption	Printing / Standby / Sleep	Less Than 460/75/5WH
Noise Level	Printing / Standby / Sleep	Less Than 50/30dB
Power Save Toner Save		



- Up to 16 pages per minute print speed
- 2400x600dpi resolution
- 16MB standard memory, expandable to up to 144MB
- "Hi-Speed USB 2.0" and Parallel ports as standard/ Optional external network connectivity

- Optimised drivers for Windows[®]95/98/Me/ NT[®]4.0/2000/ XP. Mac OS[™] 8.6-9.2, OS X 10.1 - 10.2 DOS compatible
- PCL[®]6, BR-Script[®] 3 (PostScript[®] Level 3 Language Emulation), IBM[®] Proprinter XL, Epson[®]FX-850 emulations
- 250 sheet paper cassette, 50 sheet multi-purpose tray
- Optional 250 sheet lower tray
- Easy replacement, long life supplies

Contact:

At your side.
brother®

Brother UK Ltd.,

Audenshaw, Manchester M34 5JD

Tel: +44 (0)870-830 4000 Fax: +44 (0)870-830 4031

Web-site: www.brother.co.uk

Your calls to us may be monitored or recorded for training purposes.

Specification correct at time of going to print. Brother is a registered trademark of Brother Industries Ltd. Brand product names are registered trademarks of their respective companies.